

1190 S.E. Flightline Drive, Warrenton, Oregon 97146-9692 1-800-535-8767 • 503-861-2288 • Fax 503-861-2283 E-mail: sales@lektro.com http://www.lektro.com

# Model AP8850SDA **AIRCRAFT TOWING VEHICLE** FOR AIRCRAFT UP TO 120,000 LBS/54,432 KG

Dual facing Operator's Helm

(optional).

### AP8850SDA FEATURES:

Vehicle Drive: 45.3 HP/33.8 kW, 72 VDC Traction Motor mated with Auburn/Dana 44 Differential. Limited Slip Differential, optional. **Motor Speed Control:** EV200ZX SCR with On-Board Diagnostics.

Speed controlled by Foot Throttle. Batteries: Two 36 VDC Industrial, 440 AMP-HR Batteries (6 hr rate),

wired in series. 550 AH and Single Point Watering System, optional. GPU: Built-in Independent 12/24/28 VDC / 1175 CCA Batteries and Charging System, optional.

Motive Battery Charger: External Fully Automatic 90 AMP DC / 208-480 VAC / 60 Hz / 1-PH Charger. 50 Hz, 3-PH, and/or 100 AMP, optional.

Nose Gear Lift Cradle: Patented Universal Nose Gear Lift Cradle activated by an Electric/Hydraulic Pump Assembly capable of handling dual and single wheel aircraft, and a Hold Down provision for lightnosed aircraft. Aircraft Selection System and Patented Torque Sensing Turntable Cradle Deck, optional.

Winch: Heavy-duty Hydraulic Winch with Automatic Safety Cut-Off. Winch and Strut Straps included.

Steering: Electric/Hydraulic Power Steering controlled through Automotive-type Tilt Wheel requiring minimal effort with very responsive steering action. Automatic Timer turns off power when tug not in use, increasing battery shift life.

Service Brakes: Foot Operated Hydraulic Disc-Type Service Brakes utilizing the final Wheel Drive Gearing to achieve maximum braking with minimal effort.

Parking Brake: Hand activated Electric Switch controlling Spring Applied/Hydraulic Released Calipers mounted on each Service Brake Disc.

**Drive Tires:** Single 23 x 10 x 12 18-ply Pneumatic Traction Tread. Siping, Solid-Pneumatic Tires, Auto Socks and Chains, optional. **Steer Tires:** 21 x 8-9 Solid-Pneumatic Traction Tread mounted to a

Fully Suspended Steer Axle.

Lighting: Dual Forward and Aft LED Headlights, Four Flashing Amber LED Running Lights and Amber Strobe Light mounted Center Rear. LED Brake Lights/Turn Signals, optional.

Operator's Compartment: Operator and Passenger Seats, Forward Facing, Premium Grade including Armrests (Available in Black or Light Gray). Operator's Seat features a Fully Suspended, Adjustable setting for height, fore/aft and weight. Seat Belts, Dual Facing Operator's Helm and Cab with Heater, Defroster, and Windshield Wipers, optional. Camera and Monitors: Camera at Aircraft Interface Area, with Color

Monitors at "A" and "B" Station, optional. Construction: Welded Steel Plate and Polymers preserved by Primer and Automotive High-Gloss Red or White Enamel Paint with special protective Polyurethane Coating to prevent rust, scratches and corrosion. Steel Side Rub Rails and Custom colors, optional.

### SPECIFICATIONS:

Length	207.9 in / 528.2 cm
Width	80.7 in / 205.1 cm
Height (At lowest steering tilt setting)	40 in / 103 cm
Turning Radius	
Wheel Base	0001.10040
Vehicle Speed, Empty	9MPH/14.5KPH
Vehicle Speed, Loaded (To max. Vehicle Capacity)	4 MPH / 6.4 KPH
**Lift Cradle Capacity	
Nose Gear Cradle Lifting Height	
Ground Clearance	
Shipping Weight w/o Batteries & Charger	5330 LBS / 2418 KG
Shipping Weight w/ Motive Batteries & Charger	9300 LBS / 4218 KG
Shipping Weight w/ Motive & GPU Batteries & Charger	9650 LBS / 4377 KG

\*\*Lift Capacity is calculated with 20 in / 51 cm diameter aircraft tire in lift cradle. Aircraft tire center line at 23 in / 58 cm from drive tire center line.

#### ADDITIONAL OPTIONS:

Draw Bar Pin, Specialized Aircraft Towing Adapters and Custom Highlift Adapters are available (consult factory). Illustration may show some

optional equipment. \**LEKTRO* reserves the right to make changes and improvements in products and specifications without notice or obligation. PATENT Nos. 5,151,003 / 5,302,075 / 9,067,691. Other Patents Pending.



1190 S.E. Flightline Drive, Warrenton, Oregon 97146-9692 1-800-535-8767 ● 503-861-2288 ● Fax 503-861-2283 E-mail: sales@lektro.com http://www.lektro.com

## Model **AP8850SDA** AIRCRAFT TOWING VEHICLE FOR AIRCRAFT UP TO 120,000 LBS/54,432 KG

