


Model **AP8850SDA-AL-100**

AIRCRAFT TOWING VEHICLE



AP8850SDA-AL-100 FEATURES: Vehicle Drive: 45.3 HP/33.8 kW, 72 VDC Traction Motor mated with Auburn/Dana 44 Differential. Limited Slip Differential, optional.

Motor Speed Control: EV200ZX SCR with On-Board Diagnostics.

Speed controlled by Foot Throttle.

Batteries: Two 36 VDC Industrial, 440 AMP-HR Batteries (6 hr rate), wired in series with Single Point Watering System. 550 AH, optional.

GPU: Built-in Independent 12/24/28 VDC / 1175 CCA Batteries and

Charging System, optional. Motive Battery Charger: External Fully Automatic 90 AMP DC / 208-480 VAC / 60 Hz / 3-PH Charger. 100 AMP and/or 50 Hz, optional. Nose Gear Lift Cradle: Patented Universal Nose Gear Lift Cradle activated by an Electric/Hydraulic Pump Assembly. Aircraft Selection System and Patented Torque Sensing Turntable Cradle Deck, optional. Winch: Heavy-duty Hydraulic Winch with Automatic Safety Cut-Off and RH/LH Winch/Cradle fender controls. Winch and Strut Straps included. Steering: Electric/Hydraulic Power Steering controlled through Automotive-type Tilt Wheel requiring minimal effort with very responsive steering action. Automatic Timer turns off power when tug not in use, increasing battery shift life.

Service Brakes: Foot Operated Hydraulic Disc-Type Service Brakes utilizing the final Wheel Drive Gearing to achieve maximum braking with minimal effort. Parking Brake: Hand activated Electric Switch controlling Spring Applied/Hydraulic Released Calipers mounted on each Service Brake

Drive Tires: Single 23 x 10 x 12 Solid-Pneumatic Traction Tread. Siping, Auto Socks and Chains, optional.

Steer Tires: 21 x 8-9 Solid-Pneumatic Traction Tread mounted to a Fully Suspended Steer Axle.

Lighting: Dual Forward and Aft LED Headlights, Four Flashing Amber LED Running Lights and Amber Strobe Light mounted Center Rear. LED Brake Lights/Turn Signals, optional.

Operator's Compartment: Operator and Passenger Seats, Forward Facing, Premium Grade including Armrests (Available in Black or Light Gray). Operator's Seat features a Fully Suspended, Adjustable setting for height, fore/aft and weight. Seat Belts, Dual Facing Operator's Helm and Cab with Heater, Defroster, and Windshield Wipers, optional.

Camera and Monitors: Camera at Aircraft Interface Area, with Color Monitors at "A" and "B" Station, optional.

Construction: Welded Steel Plate and Polymers preserved by Primer and Automotive High-Gloss Red or White Enamel Paint with special protective Polyurethane Coating to prevent rust, scratches and corrosion. Steel Rub Rails protect from side impact. Custom colors, optional.

SPECIFICATIONS:

Length	. 213.0 in / 541.0 cm
Width	. 82 in / 208.3 cm
Height (At lowest steering tilt setting)	.37 in / 94 cm
Turning Radius	. 180 in / 457 cm
Wheel Base	. 92.2 in / 234.2 cm
Vehicle Speed, Empty	.9MPH/14.5KPH
Vehicle Speed, Loaded (To max. Vehicle Capacity)	
**Lift Cradle Capacity	. 12,000 LBS / 5443 KG
Nose Gear Cradle Lifting Height	.9 in / 23 cm
Ground Clearance	.5 in / 12.7 cm
Shipping Weight w/o Batteries & Charger	
Shipping Weight w/ Motive Batteries & Charger	
Shipping Weight w/ Motive & GPU Batteries & Charger	

**Lift Capacity is calculated with 20 in / 51 cm diameter aircraft tire in lift cradle. Aircraft tire center line at 23 in / 58 cm from drive tire center line.

ADDITIONAL OPTIONS:

Draw Bar Pin, Specialized Aircraft Towing Adapters and Custom Highlift Adapters are available (consult factory). Illustration may show some optional equipment.

*LEKTRO reserves the right to make changes and improvements in products and specifications without notice or obligation.

PATENT Nos. 5,151,003 / 5,302,075 / 9,067,691. Other Patents Pending.

06/16



Model **AP8850SDA-AL-100**

AIRCRAFT TOWING VEHICLE FOR AIRCRAFT UP TO 120,000 LBS/54,432 KG

1190 S.E. Flightline Drive, Warrenton, Oregon 97146-9692 1-800-535-8767 ● 503-861-2288 ● Fax 503-861-2283

E-mail: sales@lektro.com http://www.lektro.com

